


NUMBER

TDS-3654


PRODUCT RANGE

ANACONDA COMPACT FITTINGS



PRODUCT DESCRIPTION

COMPACT STRAIGHT FEMALE FITTING, NPT THREAD, STAINLESS STEEL AISI-316, UL/CSA RECOGNIZED (c-UR-us)



THREAD TYPE	SEALTITE SIZE (INCH)	MIN. INTERNAL BORE (MM)	DIMENSIONS IN MM						STANDARD PACKAGE	ARTICLE NUMBER	WEIGHT (KG/100)
			A	B	C	D	E	F			
NPT 1/2"	5/16"	8,3	35	14	26	-	24	-	10	714.311.9*	5,8
NPT 1/2"	3/8"	11,0	35	14	26	-	24	-	10	714.312.9	5,6
NPT 1/2"	1/2"	14,5	36	14	29	-	27	-	10	714.316.9	6,4
NPT 3/4"	3/4"	19,4	38	15	35	-	33	-	5	714.320.9	9,1
NPT 1"	1"	24,7	41	17	45	-	42	-	5	714.326.9	15,9
NPT 1-1/4"	1-1/4"	33,3	45	17	53	-	50	-	2	714.335.9	22,0
NPT 1-1/2"	1-1/2"	38,0	52	20	62	-	58	-	2	714.340.9	32,4
NPT 2"	2"	49,0	60	23	76	-	72	-	2	714.350.9	51,2

* Size 5/16" without UL/CSA Recognition

APPLICATION AREA

Anaconda compact stainless steel AISI-316 fittings can be used with all types of Anaconda Sealrite (except CNP). This Anaconda fitting is an universal fitting and offers supreme corrosion protection in combination with a nice appearance. Because of the UL/CSA recognition (c-UR-us), the fittings are also suitable for export projects outside Europe.

MATERIAL & CONSTRUCTION:

Construction: Straight fitting consisting of 4 parts; back nut, clamping ring, flanged ferrule and body.

Material: Back nut and body are stainless steel AISI-316, clamping ring is PA6 and flanged ferrule is stainless steel AISI-304 (size 5/16" has a turned ferrule from nickel plated brass).

Temperature: -50 °C till +105 °C continuous.

Protection class: IP 67.

Colour: Metal.

CERTIFICATION & APPROVALS:

Special approvals: UL-514B and CSA C 22.2 (c-UR-us) file# E 234207.

Issued by:

Peter Rövekamp
Product Manager

Approved by:

Rob Guichelaar
Technical Manager

Date:

29 July 2025

Page:

1 of 1

