


NUMBER

TDS-3652


PRODUCT RANGE

ANACONDA COMPACT FITTINGS



PRODUCT DESCRIPTION

COMPACT STRAIGHT FEMALE FITTING, ISO METRIC THREAD, NICKEL PLATED BRASS, UL/CSA RECOGNIZED (c-UR-us)



THREAD TYPE	SEALTITE SIZE (INCH)	MIN. INTERNAL BORE (MM)	DIMENSIONS IN MM						STANDARD PACKAGE	ARTICLE NUMBER	WEIGHT (KG/100)
			A	B	C	D	E	F			
M16x1,5	5/16"	8,3	34	13	26	-	24	-	10	712.315.0*	5,1
M16x1,5	3/8"	11,0	34	13	26	-	24	-	10	712.316.1	4,9
M20x1,5	3/8"	11,0	35	14	26	-	24	-	10	712.317.1	5,4
M20x1,5	1/2"	14,5	36	14	29	-	27	-	10	712.320.1	6,0
M25x1,5	3/4"	19,4	38	15	35	-	33	-	5	712.325.1	8,5
M32x1,5	1"	24,7	41	17	45	-	42	-	5	712.332.1	15,0
M40x1,5	1-1/4"	33,3	45	17	53	-	50	-	2	712.340.1	21,2
M50x1,5	1-1/2"	38,0	52	20	62	-	58	-	2	712.350.1	31,5
M63x1,5	2"	49,0	60	23	76	-	72	-	2	712.363.1	49,0

* Size 5/16" without UL/CSA Recognition

APPLICATION AREA

Anaconda compact nickel plated brass fittings can be used with all types of Anaconda Sealtite (except CNP). This Anaconda fitting is an universal fitting and offers excellent corrosion protection in combination with a nice appearance. Because of the UL/CSA recognition (c-UR-us), the fittings are also suitable for export projects outside Europe.

MATERIAL & CONSTRUCTION:

Construction: Straight fitting consisting of 4 parts; back nut, clamping ring, flanged ferrule and body.

Material: Back nut and body are nickel plated brass, clamping ring is PA6 and flanged ferrule is galvanised steel (size 5/16" has a turned ferrule from nickel plated brass).

Temperature: -50 °C till +105 °C continous.

Protection class: IP 67.

Colour: Metal.

CERTIFICATION & APPROVALS:

Special approvals: UL-514B and CSA C 22.2 (c-UR-us) file# E 234207.

Issued by:

Peter Rövekamp
Product Manager

Approved by:

Rob Guichelaar
Technical Manager

Date:

29 July 2025

Page:

1 of 1

