


NUMBER

TDS-3694


PRODUCT RANGE

ANACONDA COMPACT FITTINGS



PRODUCT DESCRIPTION

COMPACT STRAIGHT FEMALE FITTING, ISO METRIC THREAD, STAINLESS STEEL AISI-316, UL/CSA RECOGNIZED (c-UR-us)



THREAD TYPE	SEALTITE SIZE (INCH)	MIN. INTERNAL BORE (MM)	DIMENSIONS IN MM						STANDARD PACKAGE	ARTICLE NUMBER	WEIGHT (KG/100)
			A	B	C	D	E	F			
M16x1,5	5/16"	8,3	34	13	26	-	24	-	10	712.315.9*	5,1
M16x1,5	3/8"	11,0	34	13	26	-	24	-	10	712.316.9	4,9
M20x1,5	3/8"	11,0	35	14	26	-	24	-	10	712.317.9	5,4
M20x1,5	1/2"	14,5	36	14	29	-	27	-	10	712.320.9	6,0
M25x1,5	3/4"	19,4	38	15	35	-	33	-	5	712.325.9	8,5
M32x1,5	1"	24,7	41	17	45	-	42	-	5	712.332.9	15,0
M40x1,5	1-1/4"	33,3	45	17	53	-	50	-	2	712.340.9	21,2
M50x1,5	1-1/2"	38,0	52	20	62	-	58	-	2	712.350.9	31,5
M63x1,5	2"	49,0	60	23	76	-	72	-	2	712.363.9	49,0

* Size 5/16" without UL/CSA Recognition

APPLICATION AREA

Anaconda Compact stainless steel AISI-316 fittings can be used with all types of Anaconda Sealtite (except CNP). This Anaconda fitting is an universal fitting and offers excellent corrosion protection in combination with a nice appearance. Because of the UL/CSA recognition (c-UR-us), the fittings are also suitable for export projects outside Europe.

MATERIAL & CONSTRUCTION:

Construction: Straight fitting consisting of 4 parts; back nut, clamping ring, flanged ferrule and body.

Material: Back nut and body are stainless steel AISI-316, clamping ring is PA6 and flanged ferrule is stainless steel AISI-304. (size 5/16" has a turned ferrule from nickel plated brass).

Temperature: -50 °C till +105 °C continous.

Protection class: IP 67.

Colour: Metal.

CERTIFICATION & APPROVALS:

Special approvals: UL-514B and CSA C 22.2 (c-UR-us) file# E 234207.

Issued by:

Peter Rövekamp
Product Manager

Approved by:

Rob Guichelaar
Technical Manager

Date:

16 February 2026

Page:

1 of 1

