

## ACCESSORIES FOR GALVANISED STEEL FITTINGS



Grounding ferrule, galvanised steel



| THREAD | SEALTITE SIZE (INCH) | MIN. INTERNAL BORE (MM) | DIMENSIONS IN MM |   |   |   |   | STANDARD PACKAGE | ARTICLE NUMBER | WEIGHT (KG/100) |
|--------|----------------------|-------------------------|------------------|---|---|---|---|------------------|----------------|-----------------|
|        |                      |                         | A                | B | C | D | E |                  |                |                 |
| -      | 3/8"                 | 10,4                    | -                | - | - | - | - | 50               | 297.212.0      | 1,3             |
| -      | 1/2"                 | 13,7                    | -                | - | - | - | - | 25               | 297.216.0      | 1,3             |
| -      | 3/4"                 | 18,8                    | -                | - | - | - | - | 25               | 297.220.0      | 1,4             |
| -      | 1"                   | 24,2                    | -                | - | - | - | - | 25               | 297.226.0      | 1,8             |
| -      | 1.1/4"               | 31,6                    | -                | - | - | - | - | 5                | 297.235.0      | 2               |
| -      | 1.1/2"               | 36,8                    | -                | - | - | - | - | 5                | 297.240.0      | 2,4             |
| -      | 2"                   | 48                      | -                | - | - | - | - | 5                | 297.250.0      | 2,8             |
| -      | 2.1/2"               | 58,5                    | -                | - | - | - | - | 5                | 297.263.0      | 6,4             |
| -      | 3"                   | 72                      | -                | - | - | - | - | 5                | 297.275.0      | 7,2             |
| -      | 4"                   | 95                      | -                | - | - | - | - | 1                | 297.299.0      | 7,6             |

\* From 1.1/4" the ferrule is made in aluminum



NPT lock nut, galvanised steel, with "tiger grip"



| THREAD     | SEALTITE SIZE (INCH) | MIN. INTERNAL BORE (MM) | DIMENSIONS IN MM |   |   |   |   | STANDARD PACKAGE | ARTICLE NUMBER | WEIGHT (KG/100) |
|------------|----------------------|-------------------------|------------------|---|---|---|---|------------------|----------------|-----------------|
|            |                      |                         | A                | B | C | D | E |                  |                |                 |
| NPT 1/2"   | -                    | -                       | -                | - | - | - | - | 100              | 297.416.0      | 0,5             |
| NPT 3/4"   | -                    | -                       | -                | - | - | - | - | 100              | 297.420.0      | 0,8             |
| NPT 1"     | -                    | -                       | -                | - | - | - | - | 50               | 297.426.0      | 1,3             |
| NPT 1.1/4" | -                    | -                       | -                | - | - | - | - | 50               | 297.435.0      | 1,8             |
| NPT 1.1/2" | -                    | -                       | -                | - | - | - | - | 50               | 297.440.0      | 2,2             |
| NPT 2"     | -                    | -                       | -                | - | - | - | - | 25               | 297.450.0      | 2,8             |
| NPT 2.1/2" | -                    | -                       | -                | - | - | - | - | 1                | 297.463.0      | 3,5             |
| NPT 3"     | -                    | -                       | -                | - | - | - | - | 1                | 297.475.0      | 5,6             |
| NPT 4"     | -                    | -                       | -                | - | - | - | - | 1                | 297.499.0      | 9,8             |



Neoprene ring for NPT, with galvanised steel back plate



| THREAD     | SEALTITE SIZE (INCH) | MIN. INTERNAL BORE (MM) | DIMENSIONS IN MM |   |   |   |   | STANDARD PACKAGE | ARTICLE NUMBER | WEIGHT (KG/100) |
|------------|----------------------|-------------------------|------------------|---|---|---|---|------------------|----------------|-----------------|
|            |                      |                         | A                | B | C | D | E |                  |                |                 |
| NPT 1/2"   | -                    | -                       | -                | - | - | - | - | 100              | 297.016.0      | 0,5             |
| NPT 3/4"   | -                    | -                       | -                | - | - | - | - | 100              | 297.020.0      | 0,5             |
| NPT 1"     | -                    | -                       | -                | - | - | - | - | 50               | 297.026.0      | 0,6             |
| NPT 1.1/4" | -                    | -                       | -                | - | - | - | - | 50               | 297.035.0      | 0,8             |
| NPT 1.1/2" | -                    | -                       | -                | - | - | - | - | 50               | 297.040.0      | 1,4             |
| NPT 2"     | -                    | -                       | -                | - | - | - | - | 50               | 297.050.0      | 1,4             |

## ACCESSORIES FOR GALVANISED STEEL FITTINGS



Nut with external grounding, galvanized steel



| THREAD | SEALTITE SIZE (INCH) | MIN. INTERNAL BORE (MM) | DIMENSIONS IN MM |   |    |   |   | STANDARD PACKAGE | ARTICLE NUMBER | WEIGHT (KG/100) |
|--------|----------------------|-------------------------|------------------|---|----|---|---|------------------|----------------|-----------------|
|        |                      |                         | A                | B | C  | D | E |                  |                |                 |
| -      | 3/8"                 | -                       | -                | - | 26 | - | - | 25               | 297.512.0      | 2,8             |
| -      | 1/2"                 | -                       | -                | - | 29 | - | - | 25               | 297.516.0      | 3,4             |
| -      | 3/4"                 | -                       | -                | - | 35 | - | - | 10               | 297.520.0      | -               |
| -      | 1"                   | -                       | -                | - | 42 | - | - | 5                | 297.526.0      | -               |
| -      | 1.1/4"               | -                       | -                | - | 56 | - | - | 5                | 297.535.0      | -               |
| -      | 1.1/2"               | -                       | -                | - | 64 | - | - | 1                | 297.540.0      | -               |
| -      | 2"                   | -                       | -                | - | 77 | - | - | 1                | 297.550.0      | -               |



Wire mesh, strain relief, galvanized steel



| THREAD | SEALTITE SIZE (INCH) | MIN. INTERNAL BORE (MM) | DIMENSIONS IN MM |   |    |   |   | STANDARD PACKAGE | ARTICLE NUMBER | WEIGHT (KG/100) |
|--------|----------------------|-------------------------|------------------|---|----|---|---|------------------|----------------|-----------------|
|        |                      |                         | A                | B | C  | D | E |                  |                |                 |
| -      | 3/8"                 | -                       | -                | - | 26 | - | - | 20               | 297.312.0      | 2,5             |
| -      | 1/2"                 | -                       | -                | - | 29 | - | - | 20               | 297.316.0      | 5               |
| -      | 3/4"                 | -                       | -                | - | 35 | - | - | 20               | 297.320.0      | 7,5             |
| -      | 1"                   | -                       | -                | - | 42 | - | - | 20               | 297.326.0      | 8,5             |
| -      | 1.1/4"               | -                       | -                | - | 56 | - | - | 10               | 297.335.0      | 10              |
| -      | 1.1/2"               | -                       | -                | - | 64 | - | - | 10               | 297.340.0      | 12              |
| -      | 2"                   | -                       | -                | - | 77 | - | - | 5                | 297.350.0      | 14              |

Special fittings