


Anaconda Sealtite Special

TYPE SS-HTUA GREY



ROBUST, UL LISTED, WIDE TEMPERATURE RANGE, STAINLESS STEEL AISI-316 CORE

Anaconda Sealtite Special type SS-HTUA is a robust conduit with a superior corrosion resistant AISI-316 stainless steel core and a thick, smooth PVC cover. This type is UL listed and is used to protect cables at high and low temperatures on transformers, generators, motors, actuators, valves, machinery, equipment, enclosures and installations exported to countries outside, but also inside Europe.

Material & Construction:

Construction: Stainless steel AISI-316 core, square lock profile with a cotton cord packing from size 3/8" till 1", interlocked profile without cord packing from size 1-1/4" till 2", thick smooth PVC cover.

Cover specifications: PVC, sunlight and UV

resistant, suitable for outside installation and a good resistance against oil and grease.

Temperature: -45 °C till +105 °C, intermittent up to +120 °C.

Colour: Grey




Classification according to NEN-EN-IEC 61386:

Compression resistance: Class 4, Heavy (1250 N)

Impact resistance: Class 4, Heavy (6J)

Tensile strength: Class 4, Heavy (1000 N)

Protection class: IP 66 / 67 (dust-proof, water-tight)



SEALTITE	DIAMETRE		BENDING RADIUS (CL)		STANDARD CARTON		SMALL CARTON		REEL		WEIGHT
	Size (inch)	Inside (mm)	Outside (mm)	Static (mm)	Dynamic (mm)	Metre	Article No. grey	Metre	Article No. grey	Metre	
3/8"	12,6	17,8	70	85	30	312.612.1	-	-	-	-	0,40
1/2"	16,1	21,1	90	110	30	312.616.1	-	-	-	-	0,45
3/4"	21,1	26,4	115	140	30	312.620.1	-	-	-	-	0,65
1"	26,8	33,1	145	170	30	312.626.1	-	-	-	-	1,05
1-1/4"	35,4	41,8	175	215	15	312.635.1	-	-	-	-	1,20
1-1/2"	40,3	47,8	205	250	15	312.640.1	-	-	-	-	1,50
2"	51,6	59,9	240	300	15	312.650.1	-	-	-	-	2,30

Special Approvals:

UL-360 approved DXHR.E18917, NEC Article 350, NFPA 79 (2021 Edition) Section 13.5.4 LFMC and NFPA 130 (2023 Edition) section 8.6.7.4 LFMC.

Compliant with NEC Articles:

300.22 (D) Information Technology Equipment.

250.102, 250.118(5)(f) and 250.134(B) Equipment Grounding.

Suitable for hazardous locations per NEC articles

- 501.10 (B) (2) Class I Division 2
 - 502.10 (A) (2) and (B) (2) Class II Division 1 and 2
 - 503.10 (A) (3) and (B) Class III Division 1 and 2
- 350 Liquid Tight Flexible Metal Conduit (LFMC)
645.5 (E) (2) Under raised floors.